


Series 2, Gas hob, 60 cm, Enamel, White PBP6B2K60



Optional accessories

HEZ32WA00	Wireless food thermometer
HEZ9SE040	4 pieces Set

The gas hob with easy cleaning thanks to much more space between the side-mounted knobs.

- **Ergonomic sword dials:** with raised center for precise adjustments.
- **Wider dial distance:** easy, hassle-free cleaning.
- **Continuous cast-iron finish pan supports:** for maximum stability.
- **Safety gas cut-off:** ensures safety by instantly cutting off gas supply if the flame goes out.
- **Biomethane-ready:** power your gas hob with renewable gas.

Technical Data

Appliance type:	gas hob w integrated controls
Built-in / Free-standing:	Built-in
Heating type:	Gas
Number of cooking zones:	4
Type of control setting devices:	sword knobs
Required niche size for installation (HxWxD):	45 x 560-560 x 480-490 mm
Width of the appliance:	580 mm
Dimensions:	45x580x510 mm
Dimensions of the packed product (HxWxD):	141x651x578 mm
Net weight:	7.8 kg
Gross weight:	8.7 kg
Residual heat indicator:	Without
Location of control panel:	Lateral
Basic surface material:	Enamel
Color of surface:	White
Length electrical supply cord:	100 cm
EAN code:	4242005495931
Gas connection rating:	7500 W
Fuse protection:	3 A
Voltage:	220-240 V
Frequency:	50; 60 Hz



Series 2, Gas hob, 60 cm, Enamel, White PBP6B2K60

The gas hob with easy cleaning thanks to much more space between the side-mounted knobs.

Design

- Enamel surface, white
- cast iron finish pan supports with rubber feet

Usage convenience

- Design co-ordinated control dials, right: access knobs on the side with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 4 gas burners:
- Left front: high-speed burner up to 3 kW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Right rear: standard burner up to 1.75 KW (depending on gas type)
- Right front: economy burner up to 1 KW (depending on gas type)

Cleaning

- Wider distance between dials for better cleaning.


Safety

- Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE)
- NG H/E 20mbar, E+ 20/25mbar
- Natural gas H 25 mbar (HU)
- Natural gas L 25 mbar (NL)
- Liquid gas G30,31 28-30/37mbar
- Liquid gas G30 37 mbar (PL)
- Liquid gas 50 mbar
- Pre-set for natural gas
- Nozzle set for LPG jets included. Connection to 28-30/37 mbar bottled gas. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): 51.8 x 580 x 510
- Required niche size for installation (HxWxD mm) : 45 x 560 x (480 - 490)
- Min. worktop thickness: 20 mm
- Power cord: 1 m
- Connected load: 7.5 KW

Series 2, Gas hob, 60 cm, Enamel, White
PBP6B2K60



A: Min. distance from the hob cut-out to the wall

B: Position of gas connection in the cut-out

C: With fitted oven underneath possibly more; see space requirements for the oven

For worktop thickness between 12 mm to 20 mm need additional spacer, contact customer service for details